


## LED Panel - Double Emission

Structure : Aluminum frame powder coated white. Pure white diffuser for soft light distribution. LED are positioned on the side. SMD with middle power LED. Laser printed PMMA light guide and 95% reflective film, CRI >90 on request. Dimmable and Dali driver on request.

Model: TP-14-42DE , Dimensions: L1195×W295×H18mm , Angle: 360°




**Photometric Data**  
Model:TP-14-42DE  
Power:42W  
Angle:360°

CODE	SYSTEM POWER [W]	TOTAL LUMINOUS FLUX [Lm]	CRI	CCT [K]	WEIGHT [Kg]
TP-14-42DE	42	3600	83	3000	5.45
TP-14-42DE	42	3600	83	4000	5.45
TP-14-42DE	42	3600	83	5000	5.45
TP-14-42DE[HE]	42	3300	90	3000	5.45
TP-14-42DE[HE]	42	3400	90	4000	5.45
TP-14-42DE[HE]	42	4200	83	3000	5.45
TP-14-50DE	50	4200	83	4000	5.45
TP-14-50DE	50	4200	83	5000	5.45
TP-14-50DE[HE]	50	3800	90	3000	5.45
TP-14-50DE[HE]	50	4000	90	4000	5.45
TP-14-65DE	65	5300	83	3000	5.45
TP-14-65DE	65	5500	83	4000	5.45
TP-14-65DE	65	5500	83	5000	5.45
TP-14-65DE[HE]	65	5100	90	3000	5.45
TP-14-65DE[HE]	65	5300	90	4000	5.45



## LED Panel

Model: TP-22 , Dimensions: L595×W595×H11.5mm , Power: 30W / 38W / 42W



**Photometric Data**  
Model:TP-22-38  
Power:38W  
Angle:112°


CODE	SYSTEM POWER [W]	TOTAL LUMINOUS FLUX [Lm]	CRI	CCT [K]	WEIGHT [Kg]
TP-22-30	30	2400	80	3000/4000/5000	5.45
TP-22-38	38	3000	80	3000/4000/5000	5.45
TP-22-42	42	3200	80	3000/4000/5000	5.45
TP-22-30HE	30	2800	83	3000/4000/5000	5.45
TP-22-38HE	38	3400	83	3000/4000/5000	5.45
TP-22-42HE	42	3600	83	3000/4000/5000	5.45



## Recessed Luminaires

Structure : 0.6 Sheet steel powder coated white. LED are positioned behind the diffuser. Aluminum PCB with middle power LED. Micro-perforated steel powder coated white. Dimmable and Dali driver on request.

Model: TR2-22 , Dimensions: 595×595×55mm , Power: 38W




**Photometric Data**  
Model:TR2-22-38  
Power:38W  
Angle:75°

CODE	SYSTEM POWER [W]	TOTAL LUMINOUS FLUX [Lm]	CRI	CCT [K]	WEIGHT [Kg]
TR2-22-38	38	2900	80	3000	4.46
TR2-22-38	38	3000	80	4000	4.46
TR2-22-38	38	3100	80	5000	4.46
TR2-22-38HE	38	3150	83	3000	4.46
TR2-22-38HE	38	3250	83	4000	4.46
TR2-22-38HE	38	3300	83	5000	4.46



Model: TR8-22 , Dimensions: 595×595×70mm , Power: 38W



**Photometric Data**  
Model:TR8-22-38  
Power:38W  
Angle:125°

CODE	SYSTEM POWER [W]	TOTAL LUMINOUS FLUX [Lm]	CRI	CCT [K]	WEIGHT [Kg]
TR8-22-38	38	3000	80	3000	4.90
TR8-22-38	38	3100	80	4000	4.90
TR8-22-38	38	3200	80	5000	4.90
TR8-22-38HE	38	3300	83	3000	4.90
TR8-22-38HE	38	3400	83	4000	4.90
TR8-22-38HE	38	3500	83	5000	4.90

