

LED Surface Mount Down Light - Non Adjustable



	MZ-067-0143	MZ-010-0144	MZ-118-0145
Light Source Power	LED 6.7W COB Chip	LED 10W COB Chip	LED 12.6W COB Chip
Max.Power	8W	12W	15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Non-adjustable	Non-adjustable	Non-adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 350mA	DC 550mA	DC 450mA
Dimension	Ø75×H145mm	Ø75×H145mm	Ø75×H145mm



	TO-118-0047A	TO-017-0047A	TO-024-0384
Light Source Power	LED 12.6W COB Chip	LED 20W COB Chip	LED 24W COB Chip
Max.Power	15W	22W	2×15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	1200/1350/1430/1540Lm	1700/1840/1980/2140Lm	2000/2170/2380/2620Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/50°	24°/32°/50°
Adjustable	Non-adjustable	Non-adjustable	Non-adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 450mA	DC 600mA	DC 700mA
Dimension	Ø95×H147mm	Ø95×H147mm	Ø95×H147mm

LED Pendant Mount Down Light



	DD-067-0107	DD-010-0108	DD-118-0109
Light Source Power	LED 6.7W COB Chip	LED 10W COB Chip	LED 12.6W COB Chip
Max.Power	8W	12W	15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Non-adjustable	Non-adjustable	Non-adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 350mA	DC 550mA	DC 450mA
Dimension	Ø75×H142mm	Ø75×H142mm	Ø75×H149mm



	DD-118-0049A	DD-017-0049A	DD-024-0385
Light Source Power	LED 12.6W COB Chip	LED 20W COB Chip	LED 24W COB Chip
Max.Power	15W	22W	26W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	1200/1350/1430/1540Lm	1700/1840/1980/2140Lm	2000/2170/2380/2620Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	20°/30°/50°	20°/30°/50°
Adjustable	Non-adjustable	Non-adjustable	Non-adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 450mA	DC 600mA	DC 700mA
Dimension	Ø95×H166mm	Ø95×H166mm	Ø95×H166mm