

## Outdoor Lighting

### PUK (Made in Italy)

#### 706004 & 706005 **Hydrotech Surface Mount Round Down Light**

Round downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper free aluminum body, tempered safety glass, moulded silicon gasket and stainless screws. Built-in LED driver 220-240V 50-60Hz, with 1xCOB "CXA 1512" CREE LED.



#### Construction

- \*Material: High corrosion resistance die-cast copper-free aluminum body
- \*Coating : polyester powder coating finished.
- \*Electronic transformer 220/240V 50/60Hz included
- \*Stainless steel screws
- \*Silicon rubber gasket
- \*Tempered safety glass
- \*0.5M neoprene power cable included

EN60598-1/CE

P/N: 706004

P/N: 706005



**IP65**

Made in Italy





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (Lm)	LUMINOUS EFFICACY (Lm/w)	COLORS OPTIONS
13 WATT <b>P/N: 706004</b> 220-240V 50-60HZ ELECTRONIC IP65 0.95 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHTIE	M 30°	1.290	99.23	TEXTURED GREY
26 WATT <b>P/N: 706005</b> 220-240V 50-60HZ ELECTRONIC IP65 2.30 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHTIE	M 30°	2.500	96.15	TEXTURED GREY

#### 706006 & 706007 **Hydrotech Surface Mount Square Down Light**

Square downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper free aluminum body, tempered safety glass, moulded silicon gasket and stainless screws. Built-in LED driver 220-240V 50-60Hz, with 1xCOB "CXA 1512" CREE LED.

#### Construction

- \*Material: High corrosion resistance die-cast copper-free aluminum body
- \*Coating : polyester powder coating finished.
- \*Electronic transformer 220/240V 50/60Hz included
- \*Stainless steel screws
- \*Silicon rubber gasket
- \*Tempered safety glass
- \*0.5M neoprene power cable included



**IP65**

Made in Italy

EN60598-1/CE

P/N: 706006

P/N: 706007

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (Lm)	LUMINOUS EFFICACY (Lm/w)	COLORS OPTIONS
13 WATT <b>P/N: 706006</b> 220-240V 50-60HZ ELECTRONIC IP65 1.15 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHTIE	M 30°	1.290	99.23	TEXTURED GREY
26 WATT <b>P/N: 706007</b> 220-240V 50-60HZ ELECTRONIC IP65 2.50 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHTIE	M 30°	2.500	96.15	TEXTURED GREY