

## LED Square Recessed Gimbal Down Light ( Spot Effect )

### High Power Series



	TH-030-0301	TH-038-0245
Light Source Power	LED 30W COB Chip	LED 38W COB Chip
Max.Power	32W	42W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	2540/2760/2970/3210Lm	3116/3382/3890/4830Lm
CRI	Ra80/Ra70	Ra80/Ra70
Beam angle	16°/28°/40°	16°/28°/40°
Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC850mA,35V	DC1200mA,31V
Cut out	SQ 175mm	SQ 175mm
Dimension	SQ200×H198mm	SQ200×H198mm



	TH-030-0302	TH-038-0246
Light Source Power	LED 2×30W COB Chip	LED 2×38W COB Chip
Max.Power	2×32W	2×42W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	2540/2760/2970/3210Lm	3116/3382/3890/4830Lm
CRI	Ra80/Ra70	Ra80/Ra70
Beam angle	16°/28°/40°	16°/28°/40°
Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC850mA,35V	DC1200mA,31V
Cut out	L365×W175mm	L365×W175mm
Dimension	L400×W200×H198mm	L400×W200×H198mm

## LED Square Recessed Down Light ( Spot Effect ) - Adjustable



	TH-067-0091	TH-010-0093	TH-118-0095
Light Source Power	LED 6.7W COB Chip	LED 10W COB Chip	LED 12.6W COB Chip
Max.Power	8W	12W	15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC350mA	DC550mA	DC450mA
Cut out	SQ 105mm	SQ 105mm	SQ 105mm
Dimension	Ø115×H91mm	Ø115×H106mm	Ø115×H106mm



	TH-067-0092	TH-010-0094	TH-118-0096
Light Source Power	LED 2×6.7W COB Chip	LED 2×10W COB Chip	LED 2×12.6W COB Chip
Max.Power	2×8W	2×12W	2×15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/50°	24°/32°/50°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC350mA	DC550mA	DC450mA
Cut out	L215×W100mm	L215×W100mm	L215×W100mm
Dimension	L230×W115×H91mm	L230×W115×H91mm	L230×W115×H91mm