

Indoor Lighting

LED Square Recessed Gimbal Down Light (Spot Effect)

Low Power Series



	TH-067-0231	TH-010-0233	TH-118-0235
Light Source Power	LED 6.7W COB Chip	LED 10W COB Chip	LED 12.6W COB Chip
Max.Power	8W	12W	15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 350mA	DC 550mA	DC 450mA
Cut out	SQ 110mm	SQ 110mm	SQ 110mm
Dimension	SQ135×H133mm	SQ135×H133mm	SQ135×H133mm



	TH-067-0232	TH-010-0234	TH-118-0236
Light Source Power	LED 2×6.7W COB Chip	LED 2×10W COB Chip	LED 2×12.6W COB Chip
Max.Power	2×8W LED	2×12W LED	2×15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 350mA	DC 550mA	DC 450mA
Cut out	L210×W110mm	L210×W110mm	L210×W110mm
Dimension	L230×W130×H133mm	L230×W130×H133mm	L230×W130×H133mm

Mid Power Series



	TO-118-0131	TO-017-0133	TO-267-0235
Light Source Power	LED 12.6W COB Chip	LED 20W COB Chip	LED 26.7W COB Chip
Max.Power	15W	22W	28W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	1200/1350/1430/1540Lm	1700/1840/1980/2140Lm	2010/2100/2230/2320Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/50°	24°/32°/50°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 450mA	DC 660mA	DC 700mA
Cut out	SQ 150mm	SQ 150mm	SQ 150mm
Dimension	SQ170×H153mm	SQ170×H153mm	SQ170×H153mm



	TO-118-0132	TO-017-0134	TO-267-0136
Light Source Power	LED 2×12.6W COB Chip	LED 2×20W COB Chip	LED 2×26.7W COB Chip
Max.Power	2×15W LED	2×22W LED	2×28W LED
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	1200/1350/1430/1540Lm	1700/1840/1980/2140Lm	2010/2100/2230/2320Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/50°	24°/32°/50°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 450mA	DC 600mA	DC 700mA
Cut out	L285×W150mm	L285×W150mm	L285×W150mm
Dimension	L310×W170×H153mm	L310×W170×H153mm	L310×W170×H153mm