

## Indoor Lighting

### LED Surface Mount Down Light - Adjustable

#### Low Power Series



	MZ-067-0285	MZ-010-0287	MZ-118-0289
Light Source Power	LED 6.7W COB Chip	LED 10W COB Chip	LED 12.6W COB Chip
Max.Power	8W	12W	15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 350mA	DC 550mA	DC 450mA
Dimension	SQ100×H135mm	SQ100×H135mm	SQ100×H135mm



	MZ-067-0286	MZ-010-0288	MZ-118-0290
Light Source Power	LED 2×6.7W COB Chip	LED 2×10W COB Chip	LED 2×12.6W COB Chip
Max.Power	2×8W	2×12W	2×15W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	510/540/680/750Lm	760/792/1071/1130Lm	1200/1350/1430/1540Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 350mA	DC 550mA	DC 450mA
Dimension	L180×W100×H136mm	L180×W100×H136mm	L180×W100×H136mm

### LED Surface Mount Down Light - Adjustable

#### Mid Power Series



	MZ-118-0277	MZ-010-0279	MZ-267-0281
Light Source Power	LED 12.6W COB Chip	LED 20W COB Chip	LED 26.7W COB Chip
Max.Power	15W	22W	28W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	1200/1350/1430/1540Lm	1700/1840/1980/2140Lm	2010/2100/2230/2320Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/45°	24°/32°/45°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 450mA	DC 600mA	DC 700mA
Dimension	SQ140×H146mm	SQ140×H146mm	SQ140×H146mm



	MZ-118-0278	MZ-017-0280	MZ-267-0282
Light Source Power	LED 2×12.6W COB Chip	LED 2×20W COB Chip	LED 2×26.7W COB Chip
Max.Power	2×15W	2×22W	2×28W
CCT	2700/3000/4000/5000K	2700/3000/4000/5000K	2700/3000/4000/5000K
Lumen	1200/1350/1430/1540Lm	1700/1840/1980/2140Lm	2010/2100/2230/2320Lm
CRI	Ra80/Ra70	Ra80/Ra70	Ra80/Ra70
Beam angle	24°/32°/45°	24°/32°/50°	24°/32°/50°
Adjustable	Adjustable	Adjustable	Adjustable
Voltage	220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Current	DC 450mA	DC 600mA	DC 700mA
Dimension	L280×W140×H146mm	L280×W140×H146mm	L280×W140×H146mm